

## MEDIUM DUTY COMPETITIVE COMPARISON

**Isuzu Trucks go head-to-head with the competition:**



### NQR Advantages Over Dodge Ram 5500



**Ram 5500:**

- Ram 5500 competes against NQR
- 4 wheelbase choices with regular cab
- 19,500 lb. GVWR except for 18,750 lb. GVWR with 60 inch CA
- Cummins 6.7L I6 diesel standard
- Regular cab or Quad Cab choices
- Available 4WD with manual or electric controls
- 6-speed manual standard; optional 6-speed automatic
- Ram 5500 uses conventional pickup cab shared with light duty models
- No tilt cab -- difficult engine accessibility



**NQR Advantages:**

- Maximum effective CA of 177.5 in vs. 120 in. CA for Ram 5500. N-Series can accommodate bodies to 22 ft. in length vs a maximum 18 ft. on Ram 5500
- Much greater driver visibility out larger windows and with much shorter front sight lines for ease of maneuverability. Isuzu front sight line of 8.6 feet to ground. Dodge is more than 20 feet
- Lighter weight truck has comparable payload.
- Contributes to fuel efficiency loaded or unloaded. Example: NQR with 120-in. CA has 188 lb. higher payload, with 1550 lb. lighter GVWR
- Available Vehicle Health Reports allows Isuzu fleet to monitor drivers and vehicle service needs. Not available on Dodge
- Standard cruise control, power windows and door locks on Isuzu are all optional on Dodge
- Base vehicle warranty on Isuzu is 3 years/unlimited miles. Dodge base warranty is 3 years/36,000 miles
- Tilt cab allows easy maintenance and servicing (limited engine access on Ram 5500)
- Tighter turning diameter (curb-to-curb) for comparable cab-to-axle ratio (33.5 ft./109.0 in. WB vs. 44.9 ft./143.8 in. WB ) improves maneuverability
- Reverse Elliot I-Beam front axle is strong and helps lower vehicle height with dropped center section vs. Dodge with straight tubular axle and coil springs
- Wider door opening for easy entry and exit (85 degree vs. 70 degree)
- Durable tricote breathable woven seat material is comfortable and long lasting (solid vinyl is standard on Ram 5500)
- Standard tilt and telescopic steering column contributes to driver comfort (tilt-only steering wheel on Ram 5500)
- Grab handle to assist entry and exit contributes to safety on the job (not available on Ram)
- Longer scheduled maintenance intervals helps reduce downtime and service costs (every 10,000 mi. vs. every 6,000 mi.)
- Wide, self-cleaning step on NPR vs. no steps on Dodge

SPECIFICATIONS		
	<b>Isuzu NQR</b>	<b>Dodge Ram 5500</b>
GVWR	17,950 lb.	19,500 lb.
Engine type (gas)	SOHC I-4	I-6 Cummins
Displacement (gas)	5.2L	6.7L
HP, gas	NA	NA
Torque, gas	NA	NA
HP, diesel (MT)	175 @ 2400	305 @ 2900
HP, diesel (AT)	205 @ 2400	305 @ 2900
Torque, diesel (MT)	387 @ 1850	610 @ 1600
Torque, diesel (AT)	441 @ 1850	610 @ 1600
Clutch, in.	12.8	12.5
Transmission, gas	NA	NA
Transmission, diesel	6ODA Aisin	6ODM
Alternator, amp (gas)	110	136
Steering	18.8-20.9:1 power	12.5:1 power
Front axle, lb.	6,830	7,000 tube beam
Front springs, lb.	8,440 taperleaf	7,000 coil
Rear axle, lb.	14,550	13,500
Rear springs, lb.	14,550 multileaf	13,500 multileaf
Wheels	19.5 x 6 in. 6-bolt	19.5 x 6 in. 8-bolt
Tires	225/70R-19.5F	225/70R-19.5F
Brakes, front	14.3 in. disc	15.35 in. disc
Brakes, rear	12.6 x 4.72 in. drum	15.35 in. disc
Frame, psi	44,000	50,000
Frame width, in	33.5	34
Frame section modulus	7.20 cu. in.	NA
Frame RBM	316,800	NA
Battery, CCA (gas)	2x750	2x750
Fuel tank, gal.	30 in-frame	52 in-frame
Seating	Driver & 2 pass.	40/20/40
Mirrors, in.	8x17	7x10
WB/CA (effective)	109.0/80.0	144.5/60.2
	132.5/103.5	168.5/84.2
	150.0/121.0	192.5/108.2
	176.0/147.0	204.5/120.2
	200.0/171.0	
WB/Turning Diameter (curb-to-curb, ft.)	109.0/33.5	144.5/40.1
	132.5/40.7	168.5/45.7
	150.0/45.3	192.5/51.4
	176.0/51.9	204.5/54.2
	200.0/58.5	
WB/Body lengths	109.0/10, 12	144.5/8, 9
	132.5/14	168.5/10, 11, 12
	150.0/16, 18	192.5/14, 16
	176.0/20	204.5/16, 18
	200.0/22	

STANDARD EQUIPMENT		
	<b>Isuzu NQR</b>	<b>Dodge Ram 5500</b>
Vehicle Health Reports	Standard	Not Available
50 State Clean Idle	Standard	Standard
Drop-design windows	Standard	Not Available
Exhaust brake	Standard	Standard
Tilt/telescopic steering column	Standard	Standard Tilt
Tricot fabric	Standard	Optional Fabric
Tilt cab	Standard	Not Available
Folding center seat	Standard	Standard
Daytime running lamps	Standard	Optional
Cruise control	Standard	Optional
Air conditioning	Optional	Optional
PTO prep.	Standard	Optional
Power windows	Standard	Optional
Power door locks	Standard	Optional
Floor mat	Standard	Standard
Tachometer	Standard	Standard
Convex mirrors	Standard	Standard
OPTIONAL EQUIPMENT		
	<b>Isuzu NQR</b>	<b>Dodge Ram 5500</b>
Engine block heater	Optional	Optional
Engine oil pan heater	Optional	
Limited slip differential	Optional	Optional
AM/FM/CD	Optional	Standard
Air deflector	Optional	
Spare wheel	Optional (Dealer Installed)	Optional
Side mounted fuel tank	Optional	
Engine protection system	Optional	
Engine hour meter	Optional	
Backup alarm	Optional	
Chrome wheel sim.	Optional	
Heated mirrors	Optional	Optional
WARRANTY		
	<b>Isuzu NQR</b>	<b>Dodge Ram 5500</b>
Base warranty, diesel	36 months/unlimited mileage	36 months/36,000 miles
Base warranty, gas	NA	NA
Engine warranty, diesel	36 months/unlimited mileage	60 months/100,000 miles
Engine warranty, gas	NA	NA

© 2008 Isuzu Commercial Truck of America. All rights reserved. Information contained herein is intended for use by Isuzu and GM Sales Consultants only. The information presented in this release was correct at the time of printing. Isuzu Commercial Truck of America reserves the right to make changes in color, prices, materials, equipment, specifications, warranties and models without notice or obligation. Some features shown or described are optional equipment items that are required in combination with other options. GMC, Chevrolet, General Motors Corp., GM and DEX-COOL are registered trademarks of Isuzu Commercial Truck of America. Produced by Sandy Corporation.