

# NPR-HD

14,500 LBS. GVWR  
CLASS 4



NPR-HD shown with optional Cat Cage

<b>GVWR/GCWR</b>	14,500/20,500 lbs.
<b>BODY/PAYLOAD ALLOWANCE</b>	8,237-8,947 lbs.
<b>GAWR</b>	
Front	6,630 lbs.
Rear	11,020 lbs.
<b>FRONT AXLE CAPACITY</b>	6,830 lbs.
<b>REAR AXLE CAPACITY</b>	14,550 lbs.
Ratio	4.300
<b>SUSPENSION F/R SPRINGS</b>	Tapered/Multi-Leaf
Capacity	6,830/12,900 lbs.
<b>SERVICE BRAKES</b>	
Front/Rear	4-Channel ABS Disc Brakes
<b>FRAME RAIL</b>	
Section Modulus	7.20 in. <sup>3</sup>
Resistance Bending Moment	316,800 lb.-in.
<b>TRANSMISSION</b>	6L90 6-speed auto. with double overdrive and lock-up converter
<b>ENGINE</b>	GMPT L8T (Gen V), V8 Gasoline
Displacement	6.6L (400 in. <sup>3</sup> )
Engine Power	350hp @ 4,500 rpm
Engine Torque	425 lb.-ft. @ 3,800 rpm
<b>LIMITED SLIP DIFFERENTIAL</b>	Optional
<b>ALTERNATOR</b>	170-amp
<b>BATTERIES</b>	1 Maintenance-Free 750-CCA
<b>TIRES LRR</b> (Low Rolling Resistance)	225/70R19.5F/G (12/14-pr) Standard
<b>STEERING</b>	Integral Hydraulic Power
<b>STEERING COLUMN</b>	Tilt and Telescopic
<b>FUEL TANK</b>	38.6 gal. in-frame

## 2023 ISUZU N-SERIES

### STANDARD CAB

Wheelbase (in.)	Cab to Axle (in.)	Cab to End of Frame (in.)	Back of Cab (in.)	Overall Length (in.)	Body Length (ft.)
109.0	86.5	129.6	7.7	200.5	10-12
132.5	110.0	153.1	7.7	224.0	14
150.0	127.5	170.6	7.7	241.5	16-18
176.0	153.5	196.6	7.7	267.5	18-20

### CREW CAB

150.0	88.5	131.6	5.0	241.5	12
176.0	114.5	157.6	5.0	267.5	16

